

CASES
1120
Case



Black



Silver



Orange



Yellow



Blue



OD Green*



Desert Tan

*OD Green available upon request (minimum quantities apply)



1120 Case

- ~ Watertight, crushproof, and dust proof
- ~ Open cell core with solid wall design - strong, light weight
- ~ O-ring seal
- ~ Automatic Pressure Equalization Valve
- ~ Stainless steel hardware
- ~ Pick N Pluck[®] with convoluted lid foam
- ~ Lifetime Guarantee of Excellence

1120 Case Configurations

| Cat. # | Description |
|--------|---------------------|
| 1120 | 1120 Case |
| 1120NF | 1120 Case (No foam) |

1120 Case Specifications

Exterior Dimensions (L x W x D)

8.12" x 6.56" x 3.56" (20.6 x 16.7 x 9 cm)

Lid Depth

0.50" (1.3 cm)

Weight with foam

1.23 lbs. (0.56 kg)

Range Temperature

-40 / 210° F
(-40 / 99° C)

1120 Case Certificates

- ~ IP67 (1 meter submersion for 30 minutes)
- ~ Def Stan 81-41/STANAG 4280

1120 Case Accessories

| Cat. # | Description |
|--------|---------------------------------|
| 1120PF | Special Application Panel Frame |
| 1121 | 3 pc. Replacement Foam Set |
| 1123 | Replacement O-ring |

Interior Dimensions (L x W x D)

7.25" x 4.75" x 3.06" (18.4 x 12.1 x 7.8 cm)

Bottom Depth

2.56" (6.5 cm)

Weight without foam

1.17 lbs. (0.53 kg)

Total Depth

3.06" (7.8 cm)

Buoyancy Max.

5 lbs.
(2.27 kg)