

**CASES**  
**1150**  
**Case**



Black



Silver



Orange



Yellow



Blue



OD Green\*



Desert Tan

\*OD Green available upon request (minimum quantities apply)



**1150 Case**

- ~ Watertight, crushproof, and dust proof
- ~ Open cell core with solid wall design - strong, light weight
- ~ O-ring seal
- ~ Automatic Pressure Equalization Valve
- ~ Stainless steel hardware
- ~ Pick N Plucki™ with convoluted lid foam
- ~ Lifetime Guarantee of Excellence

**1150 Case Configurations**

Cat. #	Description
1150	1150 Case
1150NF	1150 Case (No foam)

**1150 Case Specifications**

**Exterior Dimensions (L x W x D)**

9.12" x 7.56" x 4.37" (23.2 x 19.2 x 11.1 cm)

**Lid Depth**

0.75" (1.9 cm)

**Weight with foam**

1.98 lbs. (0.9 kg)

**Range Temperature**

-40 / 210° F  
(-40 / 99° C)

**1150 Case Certificates**

- ~ IP67 (1 meter submersion for 30 minutes)
- ~ Def Stan 81-41/STANAG 4280

**1150 Case Accessories**

Cat. #	Description
1150PF	Special Application Panel Frame
1151	3 pc. Replacement Foam Set
1153	Replacement O-ring

**Interior Dimensions (L x W x D)**

8.18" x 5.68" x 3.62" (20.8 x 14.4 x 9.2 cm)

**Bottom Depth**

2.87" (7.3 cm)

**Weight without foam**

1.76 lbs. (0.8 kg)

**Total Depth**

3.62" (9.2 cm)

**Buoyancy Max.**

8 lbs.  
(3.63 kg)