

CASES
1200
Case



*OD Green available upon request (minimum quantities apply)

1200 Case

- ~ Watertight, crushproof, and dust proof
- ~ Easy open Double Throw latches
- ~ Open cell core with solid wall design - strong, light weight
- ~ O-ring seal
- ~ Automatic Pressure Equalization Valve
- ~ Stainless steel hardware
- ~ Pick N Plucki™ with convoluted lid foam
- ~ Lifetime Guarantee of Excellence

1200 Case Configurations

Cat. #	Description
1200	1200 Case
1200NF	1200 Case (No foam)

1200 Case Specifications

Exterior Dimensions (L x W x D)

10.62" x 9.68" x 4.87" (27 x 24.6 x 12.4 cm)

Lid Depth

1.18" (3 cm)

Weight with foam

2.87 lbs. (1.3 kg)

Range Temperature

-40 / 210° F
(-40 / 99° C)

1200 Case Certificates

- ~ IP67 (1 meter submersion for 30 minutes)
- ~ Def Stan 81-41/STANAG 4280

1200 Case Accessories

Cat. #	Description
1200PF	Special Application Panel Frame
1201	3 pc. Replacement Foam Set
1203	Replacement O-ring

Interior Dimensions (L x W x D)

9.25" x 7.12" x 4.12" (23.5 x 18.1 x 10.5 cm)

Bottom Depth

2.93" (7.4 cm)

Weight without foam

2.65 lbs. (1.2 kg)

Total Depth

4.11" (10.4 cm)

Buoyancy Max.

12.02 lbs.
(5.45 kg)