

**CASES**  
**1300**  
**Case**



Black



Silver



Orange



Yellow



OD Green\*



Desert Tan

\*OD Green available upon request (minimum quantities apply)



**1300 Case**

- ~ Watertight, crushproof, and dust proof
- ~ Easy open Double Throw latches
- ~ Open cell core with solid wall design - strong, light weight
- ~ O-ring seal
- ~ Automatic Pressure Equalization Valve
- ~ Stainless steel hardware
- ~ Pick N Plucki™ with convoluted lid foam
- ~ Lifetime Guarantee of Excellence

**1300 Case Configurations**

Cat. #	Description
1300	1300 Case
1300NF	1300 Case (No foam)

**1300 Case Specifications**

**Exterior Dimensions (L x W x D)**

10.62" x 9.68" x 6.87" (27 x 24.6 x 17.4 cm)

**Lid Depth**

1.18" (3 cm)

**Weight with foam**

3.53 lbs. (1.6 kg)

**Range Temperature**

-40 / 210° F  
(-40 / 99° C)

**1300 Case Certificates**

- ~ IP67 (1 meter submersion for 30 minutes)
- ~ Def Stan 81-41/STANAG 4280

**1300 Case Accessories**

Cat. #	Description
1200PF	Special Application Panel Frame
1203	Replacement O-ring
1301	4 pc. Replacement Foam Set

**Interior Dimensions (L x W x D)**

9.87" x 7.00" x 6.12" (25.1 x 17.8 x 15.5 cm)

**Bottom Depth**

4.93" (12.5 cm)

**Weight without foam**

3.09 lbs. (1.4 kg)

**Total Depth**

6.11" (15.5 cm)

**Buoyancy Max.**

12.35 lbs.  
(5.6 kg)