

CASES
1450
Case



1450 Case

- ~ Watertight, crushproof, and dust proof
- ~ Easy open Double Throw latches
- ~ Open cell core with solid wall design - strong, light weight
- ~ O-ring seal
- ~ Automatic Pressure Equalization Valve
- ~ Comfortable rubber over-molded handle
- ~ Stainless steel hardware and padlock protectors
- ~ Pick N Pluck[®] with convoluted lid foam
- ~ [Personalized nameplate service available](#)
- ~ Lifetime Guarantee of Excellence

1450 Case Configurations

Cat. #	Description
1450	1450 Case
1450NF	1450 Case (No foam)
1454	1450 Case with Padded Dividers



*OD Green available upon request (minimum quantities apply)

1450 Case Specifications

Exterior Dimensions (L x W x D)

16.00" x 13.00" x 6.87" (40.6 x 33 x 17.4 cm)

Lid Depth

1.75" (4.4 cm)

Weight with foam

6.39 lbs. (2.9 kg)

Range Temperature

-40 / 210° F
(-40 / 99° C)

Interior Dimensions (L x W x D)

14.62" x 10.18" x 6.00" (37.1 x 25.8 x 15.2 cm)

Bottom Depth

4.25" (10.8 cm)

Weight without foam

5.51 lbs. (2.5 kg)

Total Depth

6.00" (15.2 cm)

Buoyancy Max.

30 lbs.
(13.61 kg)

Personalized Nameplate Available

1450 Case Certificates

- ~ IP67 (1 meter submersion for 30 minutes)
- ~ MIL C-4150J ~ Def Stan 81-41/STANAG 4280

1450 Case Accessories

Cat. #	Description
1450PF	Special Application Panel Frame
1451	3 pc. Replacement Foam Set
1453	Replacement O-ring
1455	Padded Divider Set Only