

CASES
1460
Case



1460 Case

- ~ Top lid opens up to 180° for on-the-field anti-roll stability when open
- ~ Easy open Double Throw latches
- ~ Open cell core with solid wall design - strong, light weight
- ~ O-ring seal
- ~ Automatic Pressure Equalization Valve
- ~ Comfortable rubber over-molded handles
- ~ Stainless steel hardware and padlock protectors
- ~ Pick N Pluck[®] foam
- ~ [Personalized nameplate service available](#)
- ~ Lifetime Guarantee of Excellence
- ~ Also available with EMS Organizer and Dividers
- ~ Watertight, crushproof, and dust proof

1460 Case Configurations

Cat. #	Description
1460	1460 Case
1460NF	1460 Case (No foam)
1460AALG	1460 Case (with custom foam for 9430/9435)



Black



OD Green*



Desert Tan

*OD Green available upon request (minimum quantities apply)

1460 Case Specifications

Exterior Dimensions (L x W x D)

20.85" x 12.73" x 12.75" (52.9 x 32.3 x 32.4 cm)

Lid Depth

4.91" (12.5 cm)

Weight with foam

12.48 lbs. (5.66 kg)

Range Temperature

-40 / 210° F
(-40 / 99° C)

Interior Dimensions (L x W x D)

18.54" x 9.92" x 10.92" (47.1 x 25.2 x 27.7 cm)

Bottom Depth

6.01" (15.3 cm)

Weight without foam

8.75 lbs. (3.97 kg)

Total Depth

10.92" (27.7 cm)

Buoyancy Max.

82 lbs.
(37.19 kg)

1460 Case Certificates

~ IP67 (1 meter submersion for 30 minutes)

1460 Case Accessories

Cat. #	Description
1461	Replacement Foam Set
1463	Replacement O-ring