

CASES
1560
Case



*OD Green available upon request (minimum quantities apply)

1560 Case

- ~ Retractable extension handle
- ~ Strong polyurethane wheels with stainless steel bearings
- ~ Easy open Double Throw latches
- ~ Open cell core with solid wall design - strong, light weight
- ~ O-ring seal
- ~ Automatic Pressure Equalization Valve
- ~ Comfortable rubber over-molded top and side handles
- ~ Stainless steel hardware and padlock protectors
- ~ 2 level Pick N Pluck[™] with convoluted lid foam
- ~ [Personalized nameplate service available](#)
- ~ Lifetime Guarantee of Excellence
- ~ Watertight, crushproof, and dust proof

1560 Case Configurations

Cat. #	Description
1560	1560 Case
1560NF	1560 Case (No foam)
1564	1560 Case with Padded Dividers

1560 Case Specifications

Exterior Dimensions (L x W x D)

22.06" x 17.93" x 10.43" (56 x 45.5 x 26.5 cm)

Lid Depth

2.00" (5.1 cm)

Weight with foam

20 lbs. (9.07 kg)

Range Temperature

-40 / 210° F
(-40 / 99° C)

Interior Dimensions (L x W x D)

20.37" x 15.43" x 9.00" (51.7 x 39.2 x 22.9 cm)

Bottom Depth

7.00" (17.8 cm)

Weight without foam

17 lbs. (7.71 kg)

No. of Wheels

2

Total Depth

9.00" (22.9 cm)

Buoyancy Max.

115 lbs.
(52.16 kg)

Personalized Nameplate Available

1560 Case Certificates

~ IP67 (1 meter submersion for 30 minutes)

~ Def Stan 81-41/STANAG 4280

1560 Case Accessories

Cat. #	Description
0343	Replacement O-ring
1561	4 pc. Replacement Foam Set
1562	Pick N Pluck [™] Sections Only (set of 2)
1565	Padded Divider Set Only
1569	Lid Organizer for 1560 Case