



CASES
1610
Case



1610 Case

- Retractable extension handle
- Strong polyurethane wheels with stainless steel bearings
- Easy open Double Throw latches
- Open cell core with solid wall design - strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Fold down handles
- Stainless steel hardware and padlock protectors
- 3 level Pick N Pluck™ with convoluted lid foam
- [Personalized nameplate service available](#)
- Lifetime Guarantee of Excellence
- Watertight, crushproof, and dust proof

1610 Case Configurations

Cat. #	Description
1610	1610 Case
1610NF	1610 Case (No foam)
1614	1610 Case with Padded Dividers



Black



OD Green*



Desert Tan

*OD Green available upon request (minimum quantities apply)

1610 Case Specifications

Exterior Dimensions (L x W x D)	Interior Dimensions (L x W x D)	
24.83" x 19.69" x 11.88" (63 x 50 x 30.2 cm)	21.78" x 16.69" x 10.62" (55.3 x 42.4 x 27 cm)	
Lid Depth	Bottom Depth	Total Depth
2.05" (5.2 cm)	8.57" (21.8 cm)	10.62" (27 cm)
Weight with foam	Weight without foam	Buoyancy Max.
22.3 lbs. (10.12 kg)	19.5 lbs. (8.85 kg)	119.93 lbs. (54.4 kg)
Range Temperature	No. of Wheels	
-40 / 210° F (-40 / 99° C)	2	

Personalized Nameplate Available

1610 Case Certificates

- IP67 (1 meter submersion for 30 minutes)
- Def Stan 81-41/STANAG 4280

1610 Case Accessories

Cat. #	Description
1609	Lid Organizer
1611	5 pc. Replacement Foam Set
1612	Pick N Pluck™ Sections Only (set of 3)
1615	Padded Divider Set Only
1623	Replacement O-ring