

CASES
1730
Transport Case



1730 Transport Case

- Extra deep stackable cleats
- Easy open Double Throw latches
- Open cell core with solid wall design - strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Fold down handles
- Strong polyurethane wheels with stainless steel bearings
- Stainless steel hardware and padlock protectors
- 5-piece foam set
- [Personalized nameplate service available](#)
- Lifetime Guarantee of Excellence
- Watertight, crushproof, and dust proof
- **The following custom features require a 100 pc. minimum order**
- Optional Humidity gauge changes color above 40%
- Optional Manual Pressure Equalization Valve

1730 Transport Case Configurations

Cat. #	Description
1730	1730 Transport Case
1730NF	1730 Transport Case (No foam)



Black



OD Green*



Desert Tan

*OD Green available upon request (minimum quantities apply)

1730 Transport Case Specifications

Exterior Dimensions (L x W x D) 37.50" x 27.13" x 14.37" (95.2 x 68.9 x 36.5 cm)	Interior Dimensions (L x W x D) 34.00" x 24.00" x 12.50" (86.3 x 60.9 x 31.7 cm)	
Lid Depth 2.50" (6.3 cm)	Bottom Depth 10.00" (25.4 cm)	Total Depth 12.50" (31.7 cm)
Weight with foam 38 lbs. (17.24 kg)	Weight without foam 30 lbs. (13.61 kg)	Buoyancy Max. 416 lbs. (188.69 kg)
Range Temperature -40 / 210° F (-40 / 99° C)	No. of Wheels 2	

Personalized Nameplate Available

1730 Transport Case Certificates

- IP67 (1 meter submersion for 30 minutes)

1730 Transport Case Accessories

Cat. #	Description
1731	5 pc. Replacement Foam Set
1733	Replacement O-ring