

> MAC Rack™	RACK HEIGHT U SIZE			RACK LENGTH		RACK WIDTH		LID I.D. FRONT/ BACK ¹	LENGTH O.D. ²		WIDTH O.D. ³		HEIGHT O.D. ⁴		WEIGHT		SHIPPING CUBE	
PART NO.	U	in	mm	in	mm	in	mm	in	in	mm	in	mm	in	mm	lbs	kg	ft3	m3
MR1907-02/25/02	3U	5.25	133	20	508	19	483	2.2 / 2.2	31.1	789	22.0	559	9.6	244	31	13.9	3.8	0.11
2.2 / 4.4								33.6	853	32					14.5	4.1	0.12	
4.4 / 4.4								36.1	917	33					15.1	4.4	0.13	
MR1907-02/29/02	3U	5.25	133	24	610	19	483	2.2 / 2.2	35.1	891	22.0	559	9.6	244	32	14.5	4.3	0.12
2.2 / 4.4								37.6	955	33					15.0	4.6	0.13	
4.4 / 4.4								40.1	1019	34					15.4	4.9	0.14	
MR1909-02/25/02	4U	7.00	178	20	508	19	483	2.2 / 2.2	31.1	789	22.0	559	11.4	289	33	15.2	4.5	0.13
2.2 / 4.4								33.6	853	35					15.8	4.9	0.14	
4.4 / 4.4								36.1	917	36					16.3	5.2	0.15	
MR1909-02/29/02	4U	7.00	178	24	610	19	483	2.2 / 2.2	35.1	891	22.0	559	11.4	289	35	15.6	5.1	0.14
2.2 / 4.4								37.6	955	36					16.2	5.4	0.15	
4.4 / 4.4								40.1	1019	37					16.9	5.8	0.16	
MR1910-02/25/02	5U	8.75	222	20	508	19	483	2.2 / 2.2	31.1	789	22.6	575	13.1	333	36	16.5	5.3	0.15
2.2 / 4.4								33.6	853	38					17.1	5.8	0.16	
4.4 / 4.4								36.1	917	39					17.6	6.2	0.18	

> MAC Rack™	RACK HEIGHT U SIZE			RACK LENGTH		RACK WIDTH		LID I.D. FRONT/ BACK ¹	LENGTH O.D. ²			WIDTH O.D. ³		HEIGHT O.D. ⁴		WEIGHT		SHIPPING CUBE	
PART NO.	U	in	mm	in	mm	in	mm	in	in	mm	in	mm	in	mm	lbs	kg	ft3	m3	
MR1910-02/29/02	5U	8.75	222	24	610	19	483	2.2 / 2.2	35.1	891	22.6	575	13.1	333	37	17.0	6.0	0.17	
MR1910-02/29/05								2.2 / 4.4	37.6	955					39	17.6	6.5	0.18	
MR1910-05/29/05								4.4 / 4.4	40.1	1019					40	18.1	6.9	0.20	
MR1913-02/25/02	6U	10.50	267	20	508	19	483	2.2 / 2.2	31.1	789	22.6	575	14.9	378	39	17.8	6.1	0.17	
MR1913-02/25/05								2.2 / 4.4	33.6	853					41	18.4	6.5	0.19	
MR1913-05/25/05								4.4 / 4.4	36.1	917					42	19.0	7.0	0.20	
MR1913-02/29/02	6U	10.50	267	24	610	19	483	2.2 / 2.2	35.1	891	22.6	575	14.9	378	40	18.3	6.8	0.19	
MR1913-02/29/05								2.2 / 4.4	37.6	955					42	18.9	7.3	0.21	
MR1913-05/29/05								4.4 / 4.4	40.1	1019					43	19.5	7.8	0.22	
MR1914-02/25/02	7U	12.25	311	20	508	19	483	2.2 / 2.2	31.1	789	22.6	575	16.6	422	42	19.1	6.8	0.19	
MR1914-02/25/05								2.2 / 4.4	33.6	853					43	19.5	7.3	0.21	
MR1914-05/25/05								4.4 / 4.4	36.1	917					44	20.0	7.9	0.22	
MR1914-02/29/02	7U	12.25	311	24	610	19	483	2.2 / 2.2	35.1	891	22.6	575	16.6	422	42	18.8	7.6	0.22	
MR1914-02/29/05								2.2 / 4.4	37.6	955					44	20.1	8.2	0.23	
MR1914-05/29/05								4.4 / 4.4	40.1	1019					47	21.3	8.7	0.25	
MR1917-02/25/02	9U	15.75	400	20	508	19	483	2.2 / 2.2	31.1	789	22.6	575	20.2	512	46	20.9	8.2	0.23	
MR1917-02/25/05								2.2 / 4.4	33.6	853					47	21.3	8.9	0.25	
MR1917-05/25/05								4.4 / 4.4	36.1	917					48	21.9	9.5	0.27	
MR1917-02/29/02	9U	15.75	400	24	610	19	483	2.2 / 2.2	35.1	891	22.6	575	20.2	512	47	21.3	9.3	0.26	
MR1917-02/29/05								2.2 / 4.4	37.6	955					48	21.9	9.9	0.28	
MR1917-05/29/05								4.4 / 4.4	40.1	1019					49	22.4	10.6	0.30	
MR1921-02/25/02	11U	19.25	489	20	508	19	483	2.2 / 2.2	31.1	789	22.6	575	23.6	600	50	22.6	9.6	0.27	
MR1921-02/25/05								2.2 / 4.4	33.6	853					51	23.1	10.4	0.29	
MR1921-05/25/05								4.4 / 4.4	36.1	917					52	23.6	11.2	0.32	
MR1921-02/29/02	11U	19.25	489	24	610	19	483	2.2 / 2.2	35.1	891	22.6	575	23.6	600	51	23.1	10.8	0.31	
MR1921-02/29/05								2.2 / 4.4	37.6	955					52	23.6	11.6	0.33	
MR1921-05/29/05								4.4 / 4.4	40.1	1019					53	24.1	12.4	0.35	
MR1923-02/25/02	12U	21.00	533	20	508	19	483	2.2 / 2.2	31.1	789	22.6	575	25.4	644	52	23.5	10.3	0.29	
MR1923-02/25/05								2.2 / 4.4	33.6	853					53	24.0	11.2	0.32	
MR1923-05/25/05								4.4 / 4.4	36.1	917					54	24.6	12.0	0.34	
MR1923-02/29/02	12U	21.00	533	24	610	19	483	2.2 / 2.2	35.1	891	22.6	575	25.4	644	53	24.0	11.7	0.33	
MR1923-02/29/05								2.2 / 4.4	37.6	955					54	24.6	12.5	0.35	
MR1923-05/29/05								4.4 / 4.4	40.1	1019					55	25.1	13.3	0.38	
MR1926-02/25/02	14U	24.50	622	20	508	19	483	2.2 / 2.2	31.1	789	22.6	575	28.9	734	56	25.4	11.8	0.33	
MR1926-02/25/05								2.2 / 4.4	33.6	853					57	25.7	12.7	0.36	
MR1926-05/25/05								4.4 / 4.4	36.1	917					57	25.9	13.7	0.39	
MR1926-02/29/02	14U	24.50	622	24	610	19	483	2.2 / 2.2	35.1	891	22.6	575	28.9	734	57	25.9	13.3	0.38	
MR1926-02/29/05								2.2 / 4.4	37.6	955					58	26.1	14.2	0.40	
MR1926-05/29/05								4.4 / 4.4	40.1	1019					58	26.4	15.2	0.43	

¹ - Lid Outside Dimension (O.D.) = Lid I.D. plus 1.3" on 4.4" lids and plus 1" on 2.2" lids
² - Length includes stacking ribs
³ - Width listed is calculated with plastic handles installed on sides which is standard.
3U, 4U and 5U cases come standard with stainless steel handles all around.
⁴ - Height excludes .44" stacking ribs