

CASES

iM2050

Pelican Storm Case



Black



Yellow



OD Green



iM2050 Pelican Storm Case

- Two Press & Pull Latches
- Double-layered, Soft-grip Handle
- Two Padlockable Hasps
- Vortex® Valve
- Powerful Hinges
- Meets Carry-on Regulations
- Lightweight Strong HPX® Resin
- Watertight
- Guaranteed For Life

iM2050 Pelican Storm Case Configurations

Cat. #	Description
iM2050-X0001	iM2050 Pelican Storm Case
iM2050-X0000	iM2050 Storm Case (No foam)
iM2050-X0002	iM2050 Storm Case with Padded Dividers

iM2050 Pelican Storm Case Specifications

Exterior Dimensions (L x W x D)		Interior Dimensions (L x W x D)	
11.80" x 9.80" x 4.70" (30 x 24.9 x 11.9 cm)		9.50" x 7.50" x 4.25" (24.1 x 19 x 10.8 cm)	
Lid Depth	Bottom Depth	Total Depth	
1.50" (3.8 cm)	2.75" (7 cm)	4.25" (10.8 cm)	
Weight with foam	Weight without foam	Buoyancy Max.	
3 lbs. (1.36 kg)	2.7 lbs. (1.22 kg)	16.68 lbs. (7.57 kg)	

Range Temperature

-20 / 140° F
(-29 / 60° C)

iM2050 Pelican Storm Case Certificates

• MIL-STD-810F • FED-STD-101C • ATA 300

iM2050 Pelican Storm Case Accessories

Cat. #	Description
iM-LIDSTAY	Lid Stay
iM-STRAP-S-VER2	Padded Shoulder Strap
iM-VALVE-M-B	Manual Purge Valve
iM2050-DIV	Padded Dividers
iM2050-FOAM	Replacement Foam
iM20XX-BEZEL	Base Bezel Kit