

CASES
iM2075
Pelican Storm Case



iM2075 Pelican Storm Case

- Two Press & Pull Latches
- Double-layered, Soft-grip Handle
- Two Padlockable Hasps
- Vortex® Valve
- Powerful Hinges
- Meets Carry-on Regulations
- Lightweight Strong HPX® Resin
- Watertight
- Guaranteed For Life

iM2075 Pelican Storm Case Configurations

Cat. #	Description
iM2075-X0001	iM2075 Pelican Storm Case
iM2075-X0000	iM2075 Storm Case (No foam)
iM2075-X0002	iM2075 Storm Case with Padded Dividers



Black



Yellow



OD Green

iM2075 Pelican Storm Case Specifications

Exterior Dimensions (L x W x D)		Interior Dimensions (L x W x D)	
11.80" x 9.80" x 7.70" (30 x 24.9 x 19.6 cm)		9.50" x 7.50" x 7.25" (24.1 x 19 x 18.4 cm)	
Lid Depth	1.50" (3.8 cm)	Bottom Depth	Total Depth
		5.75" (14.6 cm)	7.25" (18.4 cm)
Weight with foam	3.7 lbs. (1.68 kg)	Weight without foam	Buoyancy Max.
		3.3 lbs. (1.5 kg)	28.45 lbs. (12.9 kg)

Range Temperature

-20 / 140° F
 (-29 / 60° C)

iM2075 Pelican Storm Case Certificates

• MIL-STD-810F • FED-STD-101C • ATA 300

iM2075 Pelican Storm Case Accessories

Cat. #	Description
iM-LIDSTAY	Lid Stay
iM-STRAP-S-VER2	Padded Shoulder Strap
iM-VALVE-M-B	Manual Purge Valve
iM2075-DIV	Padded Dividers
iM2075-FOAM	Replacement Foam
iM20XX-BEZEL	Base Bezel Kit