

CAT NO.	BATTERIES (included)	WEIGHT W/ BATTERIES (KG)	LENGTH (CM)	LUMENS	RUN TIME	BEAM SPREAD	NUMBER OF LEDs	LAMP HEADS	CERTIFICATIONS	COLORS
<b>9420XL</b>	Rechargeable Lithium ion	8.4 lbs. (3.8)	62.0" (157) <sup>A</sup>	1000*, 500***	2h*, 4h***	58°	2	1	N/A	■
<b>9430</b>	Rechargeable, Sealed Lead Acid	22.65 lbs. (10.27)	32.28" (82) <sup>A</sup>	3000*, 1500***	8h*, 15h***	125°	6	1	N/A	■ ■
<b>9430SL</b>	Rechargeable, Sealed Lead Acid	22.05 lbs. (10)	32.28" (82) <sup>A</sup>	2000*, 1000***	8h*, 15h***	10°	24	1	N/A	■
<b>9435</b>	Rechargeable NiMH	17.6 lbs. (7.98)	32.28" (82) <sup>A</sup>	1500*, 750***	5h*, 10h***	90°	18	1	CI, D2	■
<b>9440</b>	Rechargeable Lithium ion	16.09 lbs. (7.3)	85" (215.8) <sup>A</sup>	5300*, 2800** 1400***	1h 30m*, 4h** 8h***	125°	12	1	N/A	■ ■
<b>9460</b>	Rechargeable, Sealed Lead Acid	61 lbs. (27.7)	79.50" (201.9) <sup>A</sup>	12,000 (variable)	3h*, 24h***	120°	10 per head	2	N/A	■ ■
<b>9460M</b>	Rechargeable, Sealed Lead Acid	64 lbs. (24.95)	79.50" (201.9) <sup>A</sup>	12,000 (variable)	3h*, 24h***	120°	10 per head	2	N/A	■ ■
<b>9470</b>	Rechargeable, Sealed Lead Acid	105 lbs. (47.6)	82.00" (208.3) <sup>A</sup>	24,000 (variable)	2h 45m*, 24h***	120°	10 per head	4	N/A	■ ■
<b>9470M</b>	Rechargeable, Sealed Lead Acid	108lbs. (49)	82.00" (208.3) <sup>A</sup>	24,000 (variable)	2h 45m*, 24h***	120°	10 per head	4	N/A	■ ■
<b>9480</b>	Rechargeable, Sealed Lead Acid	27.5 lbs. (12.47)	23.75" (60.3) <sup>A</sup>	4000*, 3000** 1000***	6h*, 8h** 28h***	125°	8	1	N/A	■ ■
<b>9490</b>	Rechargeable, Sealed Lead Acid	32 lbs. (14.51)	72" (182.8) <sup>A</sup>	6000 (variable)	3h 30m*, 12h** 24h***	125°	10	1	N/A	■ ■
<b>9500</b>	N/A	29.8 lbs. (13.52)	20.62" (52.4)	6000 (white LED) 1200 (red LED)	constant 120V	210° (diffused)	36	3	N/A	■

CAT NO.	BATTERIES	WEIGHT W/ BATTERIES (KG)	LENGTH (CM)	ANSI LIGHT OUTPUT	ANSI RUN TIME	ANSI BEAM DISTANCE (meters)	ANSI PEAK BEAM INTENSITY (candela)	ANSI IPX RATING	CERTIFICATIONS	COLORS
<b>1810</b>	4 LR 41 Alkaline (included)	0.5 oz. (0.01)	1.5" (3.8)	16	8h 30m	23	137	IPX4	N/A	■ ■ ■ ■ ■ ■ ■ ■
<b>1830</b>	3 AAAA Alkaline (included)	1.2 oz. (0.03)	6.2" (15.7)	5	32h	13	44	IPX4	CI, D1	■ ■
<b>1900</b>	2 AAA Alkaline (included)	1.6 oz. (0.05)	4.09" (10.4)	11	1h 30m	45	571	IPX7	CI, D1/CII, D2	■ ■ ■ ■ ■ ■ ■ ■
<b>1910</b>	1 AAA Alkaline (included)	1.5 oz. (0.04)	3.8" (9.6)	106*, 21***	2h 30m*, 4h***	55*, 24***	765*, 140***	IPX7	N/A	■
<b>1910</b>	1 AAA Alkaline (included)	1.5 oz. (0.04)	3.8" (9.6)	72*, 14***	1h 45m*, 4h***	64*, 28***	1031*, 198***	IPX7	N/A	■ ■ ■ ■ ■ ■ ■ ■
<b>1920</b>	2 AAA Alkaline (included)	2.2 oz. (0.06)	5.5" (14)	224*, 22***	2h 15m*, 8h 45m***	81*, 25***	1640*, 152***	IPX7	N/A	■
<b>1920</b>	2 AAA Alkaline (included)	2.2 oz. (0.06)	5.5" (14)	120*, 12***	2h 45m*, 8h 30m***	87*, 27***	1893*, 184***	IPX7	N/A	■ ■ ■ ■ ■ ■ ■ ■
<b>1930</b>	4 LR 44 Alkaline (included)	0.9 oz. (0.03)	2.64" (6.7)	12	4h 15m	17	70	IPX4	CI, D1/CII, D2	■ ■
<b>1965</b>	2 AAA Alkaline (included)	1.9 oz. (0.05)	5.48" (13.9)	34	3h 45m	45	512	IPX7	CI II III, D1	■ ■
<b>2140</b>	2 AAA Alkaline (included)	1.8 oz. (0.05)	3.5" (8.9)	13	2h	84	1761	IPX7	CI, D2	■
<b>2220</b>	2 CR2032 Lithium (included)	1 oz. (0.03)	3.5" (8.9)	9	34h	12	38	IPX4	CI, D1	■ ■ ■
<b>2300</b>	2 AA Alkaline (included)	3.4 oz. (0.1)	5.62" (14.3)	11	4h 30m	43	478	IPX4	CI, D1/CII, D2	■ ■
<b>2340</b>	2 AA Alkaline (not included)	3.5 oz. (0.1)	6.25" (15.9)	10	4h 30m	43	461	IPX4	CI II, D2	■ ■

\*High | \*\*Medium | \*\*\*Low | \*\*\*\*Downcast | <sup>A</sup> Extended Height | Additional approvals may apply. For details go to [www.pelican.com](http://www.pelican.com)

CAT NO.	BATTERIES	WEIGHT W/ BATTERIES (KG)	LENGTH (CM)	ANSI LIGHT OUTPUT	ANSI RUN TIME	ANSI BEAM DISTANCE (meters)	ANSI PEAK BEAM INTENSITY (candela)	ANSI IPX RATING	CERTIFICATIONS	COLORS
<b>1800</b>	2 C Alkaline (not included)	7.8 oz. (0.22)	6" (15.2)	21	7h	131	4370	IPX7	CI II, D2	■ ■
<b>1820</b>	2 C Alkaline (included)	8.3 oz. (0.24)	5.83" (14.8)	22	6h 45m	146	5466	IPX7	CI II III, D2	■ ■
<b>2000</b>	3 C Alkaline (not included)	12.8 oz. (0.36)	7.79" (19.8)	53	5h	158	6234	IPX7	CI, D1/CII, D2	■ ■ ■
<b>2000PL</b>	3 C Alkaline (not included)	12.8 oz. (0.36)	7.79" (19.8)	53	5h	158	6234	IPX7	CI, D1/CII, D2	■
<b>2010</b>	3 C Alkaline (not included)	13.4 oz. (0.38)	8.11" (20.6)	161	22h	160	6398	IPX7	CI II III, D1	■ ■
<b>2010PL</b>	3 C Alkaline (not included)	13.4 oz. (0.38)	8.11" (20.6)	161	22h	160	6398	IPX7	CI II III, D1	■
<b>2020</b>	3 C Alkaline (not included)	14.7 oz. (0.42)	8.75" (22.2)	75	6h 30m	113	3211	IPX7	CI, D1	■ ■
<b>2400</b>	4 AA Alkaline (included)	7.1 oz. (0.2)	6.49" (16.5)	45	3h 45m	125	3934	IPX7	CI, D1/CII, D2	■ ■ ■ ■ ■
<b>2400PL</b>	4 AA Alkaline (included)	7.1 oz. (0.2)	6.49" (16.5)	45	3h 45m	125	3934	IPX7	CI, D1/CII, D2	■
<b>2410</b>	4 AA Alkaline (included)	7.3 oz. (0.21)	7" (17.8)	183	5h 45m	184	8480	IPX7	CI II III, D1	■ ■
<b>2410PL</b>	4 AA Alkaline (included)	7.3 oz. (0.21)	7" (17.8)	183	5h 45m	184	8480	IPX7	CI II III, D1	■
<b>2430</b>	4 AA Alkaline (included)	6.1 oz. (0.17)	6.5" (16.5)	70	2h 15m	104	2766	IPX4	CI, D2	■ ■
<b>2450</b>	Rechargeable NiMH (included)	7.8 oz. (0.22)	6.5" (16.5)	35	3h 30m	122	3735	IPX7	CI II, D2	■ ■
<b>2460</b>	Rechargeable NiMH (included)	7.8 oz. (0.22)	7" (17.8)	183	5h	179	8050	IPX7	CI II, D2	■ ■
<b>3310PL</b>	3 AA Alkaline (included)	6.2 oz. (0.18)	6.14" (15.6)	378*, 39***	8h*, 202h***	196*, 62***	9580*, 961***	IPX8	N/A	■ (photoluminescent)
<b>3310ELS</b>	3 AA Alkaline (included)	6.2 oz. (0.18)	6.14" (15.6)	378*, 39***	8h*, 202h***	196*, 62***	9580*, 961***	IPX8	N/A	■ (photoluminescent)
<b>3315</b>	3 AA Alkaline (included)	6.2 oz. (0.18)	6.14" (15.6)	160	19h	144	5153	IPX7	CI II III, D1	■ ■
<b>3315R</b>	Rechargeable Lithium-Ion (included)	6.2 oz. (0.18)	6.11" (15.5)	132*, 15***	5h*, 34h***	108*, 35***	2931*, 308***	IPX7	CI, D1	■ ■
<b>3315PL</b>	3 AA Alkaline (included)	6.2 oz. (0.18)	6.14" (15.6)	160	19h	144	5153	IPX7	CI II III, D1	■ (photoluminescent)
<b>3325</b>	3 AA Alkaline (included)	6.1 oz. (0.17)	6.06" (15.4)	162	16h	144	5215	IPX7	CI, D1	■
<b>4000</b>	8 D Alkaline (not included)	74.08 oz. (2.1)	9.37" (23.8)	249	11h	106	3168	IPX7	CI II, D2	■ ■ ■
<b>9410L</b>	Rechargeable Lithium-Ion (included)	44.7 oz. (1.27)	8.75" (22.2)	1203*, 553***	4h 30m*, 10h 30m***	430*, 287***	46,328*, 20,616***	IPX4	N/A	■ ■
<b>9415</b>	Rechargeable NiMH (included)	49.3 oz. (1.4)	8.75" (22.2)	413*, 159***	4h 30m*, 12h***	325*, 201***	26352*, 10076***	IPX4	CI, D1	■
<b>2350</b>	1 AA Alkaline (included)	3.4 oz. (0.1)	4.23" (10.7)	178*, 15***	2h 15m*, 21h***	130*, 37***	4196*, 345***	IPX7	N/A	■
<b>2360</b>	2 AA Alkaline (included)	5.4 oz. (0.15)	6.2" (15.7)	375*, 29***	2h 30m*, 13h***	192*, 53***	9187*, 705***	IPX8	N/A	■
<b>2370</b>	2 AA Alkaline (included)	6.5 oz. (0.18)	6.43" (16.3)	358*, 35***	2h*, 11h***	158*, 52***	9000*, 823***	IPX7	N/A	■
<b>2380</b>	2 AA Alkaline (included)	6.6 oz. (0.19)	6.44" (16.4)	372*, 31***	3h 30m*, 13h***	167*, 46***	6967*, 527***	IPX7	N/A	■

\*High | \*\*Medium | \*\*\*Low | \*\*\*\*Downcast | <sup>A</sup> Extended Height | Additional approvals may apply. For details go to [www.pelican.com](http://www.pelican.com)

CAT NO.	BATTERIES	WEIGHT W/ BATTERIES (KG)	LENGTH (CM)	ANSI LIGHT OUTPUT	ANSI RUN TIME	ANSI BEAM DISTANCE (meters)	ANSI PEAK BEAM INTENSITY (candela)	ANSI IPX RATING	CERTIFICATIONS	COLORS
<b>2380R</b>	Rechargeable Lithium-Ion (included)	6.6 oz. (0.19)	6.48" (16.5)	305*, 30***	3h 30m*, 25h***	159*, 50***	6317*, 613***	IPX7	N/A	■
<b>3330</b>	2 CR123 Lithium (included)	3.45 oz. (0.1)	5.27" (13.4)	90	4h 45m	88	1959	IPX4	N/A	■ ■
<b>7000</b>	2 CR123 Lithium (included)	5.6 oz. (0.16)	5.31" (13.5)	602*, 311** , 64***	1h 30m*, 2h**, 16h***	233*, 165**, 75***	13604*, 6830**, 1409***	IPX7	N/A	■
<b>7060</b>	Rechargeable Lithium-Ion (included)	10.4 oz. (0.29)	8.65" (22)	368*, 150**, 18***	3h*, 9h**, 45h***	199*, 125**, 43***	9953*, 3922**, 473***	IPX4	v	■
<b>7100</b>	Lithium-Ion	4.4 oz. (0.13)	5.12" (13)	695*, 348**, 33***	1h 15m*, 1h 30m**, 9h 15m***	194*, 130**, 38***	9314*, 4247**, 358***	IPX8	N/A	■
<b>7600</b>	Lithium-Ion	7.1 oz. (0.20)	6.19" (15.7)	944*, 479**, 37***	3h 15m*, 4h 30m**, 29h***	225*, 157**, 44***	12693*, 6172**, 480***	IPX8	N/A	■
<b>8050</b>	Rechargeable NiMH (included)	17.92 oz. (0.51)	11.25" (28.6)	164	2h 15m	256	16448	IPX4	N/A	■ ■
<b>8060</b>	Rechargeable NiMH (included)	23.2 oz. (0.66)	12.67" (32.2)	803*, 447**, 25***	2h 30m*, 4h**, 69h***	359*, 265**, 62***	32252*, 17492**, 958***	IPX4	N/A	■
<b>2600</b>	4 AA Alkaline (included)	9.7 oz. (0.27)	3.81" (9.7)	18	3h 30m	27	203	IPX7	CI II III, D2	■
<b>2610</b>	3 AAA Alkaline (included)	3.2 oz. (0.09)	1.49" (3.8)	30*, 14***	19h*, 47h***	28*, 19***	194*, 91***	IPX4	CI, D1	■
<b>2620</b>	3 AAA Alkaline (included)	4.8 oz. (0.14)	2.16" (5.5)	26*, 14***	2h 15m*, 18h**	44*, 29**	491*, 216**	IPX4	CI, D1	■
<b>2640</b>	4 AA Alkaline (included)	10.9 oz. (0.31)	2.63" (6.7)	29*, 16***	2h 45m*, 17h**	46*, 20***	586*, 103***	IPX4	CI, D2	■
<b>2680</b>	4 AA Alkaline (included)	9.7 oz. (0.27)	4.64" (11.8)	79	10h	123	3789	IPX7	CI II III, D2	■
<b>2690</b>	3 AAA Alkaline (included)	4.1 oz. (0.12)	2.81" (7.1)	74	11h	92	2124cd	IPX7	CI II III, D1	■
<b>2720</b>	3 AAA Alkaline (included)	3.8 oz. (0.11)	2.48" (6.3)	200*, 12***	3h*, 103h***	82*, 20***	1684*, 103***	IPX4	N/A	■
<b>2740</b>	3 AAA Alkaline (included)	3.3 oz. (0.09)	2.25" (5.7)	66*, 36***	7h 15m*, 21h***	22*, 16***	122*, 68***	IPX4	N/A	■ ■ (translucent)
<b>2745</b>	3 AAA Alkaline (included)	3.3 oz. (0.09)	2.25" (5.7)	33*, 17***	20h*, 40h***	35*, 25***	309*, 155***	IPX4	CI, D1	■ ■
<b>2750</b>	3 AAA Alkaline (included)	3.4 oz. (0.1)	2.25" (5.7)	193*, 63***	3h*, 11h***	98*, 58***	1250*, 591***	IPX4	N/A	■ ■ (photoluminescent)
<b>2755</b>	3 AAA Alkaline (included)	3.4 oz. (0.1)	2.25" (5.7)	72*, 34***	6h*, 15***	57*, 40***	807*, 404***	IPX4	C1, D1	■ ■
<b>2760</b>	3 AAA Alkaline (included)	3.4 oz. (0.1)	2.25" (5.7)	204*, 141**, 95***, 42***	2h*, 3h 15m**, 5h***, 11h***	111*, 80**, 59***, 19***	3065*, 1606**, 861***, 88***	IPX4	N/A	■ ■ (translucent)
<b>2765</b>	3 AAA Alkaline (included)	3.4 oz. (0.1)	2.25" (5.7)	105*, 104**, 65***, 33***	4h 15m*, 4h**, 6h 15m***, 9h***	107*, 93**, 63***, 9***	2876*, 2163**, 978***, 18***	IPX4	C1, D1	■ ■
<b>2780</b>	4 AA Alkaline (included)	250 oz. (7.09)	3" (7.6)	430*, 203**, 53***	1h 30m*, 3h**, 12h***	127*, 81**, 27***	3868*, 1625**, 425***	IPX7	N/A	■ □ (photoluminescent)
<b>2780R</b>	Rechargeable Lithium-Ion (included)	250 oz. (7.09)	3" (7.6)	558*, 213**, 95***	2h*, 3h**, 7h 30m***	127*, 78**, 53***	4060*, 1540**, 695***	IPX7	N/A	■ □ (photoluminescent)
<b>2785</b>	4 AA Alkaline (included)	250 oz. (7.09)	3" (7.6)	226*, 103**, 33***	5h 45m*, 20h**, 66h***	111*, 74**, 41***	3058*, 1372**, 417***	IPX7	CI, D1	■ ■

\*High | \*\*Medium | \*\*\*Low | \*\*\*\*Downcast | ^ Extended Height | To place an order please call 817-479-8300 or contact us at www.protechcase.com.

CAT NO.	BATTERIES	WEIGHT W/ BATTERIES (KG)	LENGTH (CM)	ANSI LIGHT OUTPUT	ANSI RUN TIME	ANSI BEAM DISTANCE (meters)	ANSI PEAK BEAM INTENSITY (candela)	ANSI IPX RATING	CERTIFICATIONS	COLORS
<b>2250</b>	2 AA Alkaline (included)	0.3 oz. (0.09)	3.87" (9.8)	7	5h 30m	54	726	IPX4	CI II, D2	■
<b>3315R-RA</b>	Rechargeable Lithium-Ion (included)	6.2 oz. (0.18)	6.11" (15.5)	132*, 15***	5h*, 34h***	108*, 35***	2931*, 308***	IPX7	CI, D1	■
<b>3610</b>	4 AA Alkaline (included)	10.5 oz. (0.3)	7.51" (19.1)	183	5h 45m	184	8480	IPX7	CI II III, D1	■ ■
<b>3610PL</b>	4 AA Alkaline (included)	10.5 oz. (0.3)	7.51" (19.1)	183	5h 45m	184	8480	IPX7	CI II III, D1	■
<b>3660</b>	Rechargeable 4 AA NiMH (included)	10.56 oz. (0.3)	7.51" (19.1)	183	5h	153	5828	IPX7	CI II, D2	■ ■
<b>3700</b>	4 C Alkaline (not included)	20.32 oz. (0.58)	7" (17.8)	39*, 25 (back-up)	6h 15m*, 8h 30m (back-up)	98*, 51 (back-up)	2437*, 684 (back-up)	IPX4	CI, D2	■
<b>3700PL</b>	4 C Alkaline (not included)	20.32 oz. (0.58)	7" (17.8)	39*, 25 (back-up)	6h 15m*, 8h 30m (back-up)	98*, 51 (back-up)	2437*, 684 (back-up)	IPX4	CI, D2	■
<b>3715</b>	4 AA Alkaline (not included)	14.4 oz. (0.41)	5.36" (13.6)	233*, 113***, 31****	4h*, 7h***, 31h****	293*, 187***, 30****	21440*, 8775***, 220****	IPX4	CI, D1	■ ■
<b>3715PL</b>	4 AA Alkaline (not included)	14.4 oz. (0.41)	5.36" (13.6)	233*, 113***, 31****	4h*, 7h***, 31h****	293*, 187***, 30****	21440*, 8775***, 220****	IPX4	CI, D1	■
<b>3750</b>	Rechargeable NiCad (included)	20.48 oz. (0.58)	7" (17.8)	96*, 28 (back-up)	1h 45m*, 4h (back-up)	133*, 65 (back-up)	4468*, 1048 (back-up)	IPX4	CI, D2	■
<b>3750PL</b>	Rechargeable NiCad (included)	20.48 oz. (0.58)	7" (17.8)	96*, 28 (back-up)	1h 45m*, 4h (back-up)	133*, 65 (back-up)	4468*, 1048 (back-up)	IPX4	CI, D2	■
<b>3765</b>	Rechargeable NiMH (included)	14.6 oz. (0.41)	5.36" (13.6)	237*, 113***, 32****	3h*, 6h 30m***, 14h****	301*, 193***, 28****	22720*, 9354***, 192****	IPX4	CI, D1/CI, D2 (w/alkalines)	■ ■
<b>3765PL</b>	Rechargeable NiMH (included)	14.6 oz. (0.41)	5.36" (13.6)	237*, 113***, 32****	3h*, 6h 30m***, 14h****	301*, 193***, 28****	22720*, 9354***, 192****	IPX4	CI, D1/CI, D2 (with/alkalines)	■
<b>1960N</b>	2 AAA Alkaline (included)	1.9 oz. (0.05)	5.48" (13.9)	34	3h 30m	42	450	IPX8	N/A	■ ■ ■
<b>2010N</b>	3 C Alkaline (not included)	13.4 oz. (0.38)	8.11" (20.6)	161	22h	260	6398	IPX8	N/A	■ ■ ■
<b>2410N</b>	4 AA Alkaline (included)	7.3 oz. (0.21)	7" (17.8)	183	5h 45m	184	8480	IPX8	N/A	■ ■ ■
<b>2130</b>	2 L1154 Alkaline (included)	0.5 oz. (0.01)	1.73" (4.4)	4.7 (non ANSI)	130h (non ANSI)	N/A	N/A	IPX7	N/A	■
<b>2130IR</b>	2 L1154 Alkaline (included)	0.5 oz. (0.01)	1.73" (4.4)	N/A	65h (non ANSI)	N/A	N/A	IPX7	N/A	■
<b>2365</b>	2 AA Alkaline (not included)	9.3 oz. (0.26)	21.92" (55.7)	65	7h	81	1644	IPX4	N/A	■
<b>2490</b>	4 AA Alkaline (not included)	8.2 oz. (0.23)	12.5" (31.7)	64	12h	118	3459	IPX7	N/A	■

\*High | \*\*Medium | \*\*\*Low | \*\*\*\*Downcast | ^ Extended Height | To place an order please call 817-479-8300 or contact us at www.protechcase.com.