

1690 Protector Transport Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican[™] Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

- · Personalized nameplate service available
- · 4 strong polyurethane wheels with stainless steel bearings
- Large 2-person fold down handles
- · Watertight, crushproof, and dustproof
- 3 level Pick N Pluck[™] with convoluted lid foam
- Automatic Pressure Equalization Valve balances interior pressure, keeps water out
- · Easy open double-throw latches
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Retractable extension trolley handle
- Stainless steel padlock protectors

DIMENSIONS

Interior (L×W×D) 30.13 x 25.13" x 15.36 (76.5 x 63.8 x 39 cm) Exterior (L×W×D) 33.43 x 28.40" x 17.65 (84.9 x 72.1 x 44.8 cm) Lid Depth 2.86" (7.3 cm) **Bottom Depth** 12.14" (30.8 cm) **Total Depth** 15" (38.1 cm) Int Volume 6.73 ft3 (0.191 m3) Padlock Hole Diameter 5/16" (8 mm)

MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel
Foam	1.3 lb Polyurethane
Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven

Desert Tan

COLORS

Black

OD Green

WEIGHT

Weight With Foam	43.00 lbs (19.5 kg)
Weight Empty	34.00 lbs (15.4 kg)
Buoyancy	433.00 lbs (196.4 kg)
Master Pack Weight	52.27 lbs (23.7 kg)

PELICAN



OTHER

Wheels	4
Extendable Handle	yes
Master Pack	1
Nameplate	yes
Reduced Area	yes

TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	210°F (98.9 °C)

CERTIFICATIONS

IP67 Def Stan 81-41

Pro-Tech Case, Inc. • 1116 Jericho Court • Keller, TX 76262 Phone:1.800.714.6747 or 940-390-7102 • Fax: 817.479-6130 • Email: info@protechcase.com