



CASES

iM2975

Pelican Storm Transport Case



iM2975 Pelican Storm Transport Case

- Five Press & Pull Latches
- Three Double-layered, Soft-grip Handles
- Two Padlockable Hasps
- In-line Wheels
- Telescoping Handle
- Vortex® Valve
- Flush Powerful Hinges
- Lightweight Strong HPX® Resin
- Watertight
- Guaranteed For Life

iM2975 Pelican Storm Transport Case Configurations

Cat. #	Description
iM2975-X0001	iM2975 Pelican Storm Transport Case
iM2975-X0000	iM2975 Storm Case (No foam)
iM2975-X0002	iM2975 Storm Case with Padded Dividers



Black



OD Green

iM2975 Pelican Storm Transport Case Specifications

Exterior Dimensions (L x W x D) 31.30" x 20.40" x 15.50" (79.5 x 51.8 x 39.4 cm)	Interior Dimensions (L x W x D) 29.00" x 18.00" x 13.80" (73.6 x 45.7 x 35 cm)	
Lid Depth 2.00" (5.1 cm)	Bottom Depth 11.80" (30 cm)	Total Depth 13.80" (35 cm)
Weight with foam 29.5 lbs. (13.38 kg)	Weight without foam 22.8 lbs. (10.34 kg)	Buoyancy Max. 332.77 lbs. (150.94 kg)
Range Temperature -20 / 140° F (-29 / 60° C)	No. of Wheels 2	Retractable Handle YES

iM2975 Pelican Storm Transport Case Certificates

• MIL-STD-810F • FED-STD-101C • ATA 300

iM2975 Pelican Storm Transport Case Accessories

Cat. #	Description
iM-LIDSTAY	Lid Stay
iM-VALVE-M-B	Manual Purge Valve
iM2975-DIV	Padded Dividers
iM2975-FOAM	Replacement Foam
iM29XX-BEZEL	Base Bezel Kit
iM29XX-BEZEL-LID	Lid Bezel Kit
iM29XX-UTILITYORG	Utility Organizer