



CASES

iM3075

Pelican Storm Transport Case



iM3075 Pelican Storm Transport Case

- Seven Press & Pull Latches
- Four Double-layered, Soft-grip Handles
- Two Padlockable Hasps
- In-line Wheels
- Telescoping Handle
- Vortex® Valve
- Flush Powerful Hinges
- Lightweight Strong HPX® Resin
- Watertight
- Guaranteed For Life

iM3075 Pelican Storm Transport Case Configurations

Cat. #	Description
iM3075-X0001	iM3075 Pelican Storm Transport Case
iM3075-X0000	iM3075 Storm Case (No foam)
iM3075-X0002	iM3075 Storm Case with Padded Dividers



Black



OD Green

iM3075 Pelican Storm Transport Case Specifications

Exterior Dimensions (L x W x D) 33.30" x 24.40" x 19.30" (84.5 x 62 x 49 cm)	Interior Dimensions (L x W x D) 29.80" x 20.80" x 17.80" (75.7 x 52.8 x 45.2 cm)	
Lid Depth 4.00" (10.2 cm)	Bottom Depth 13.75" (34.9 cm)	Total Depth 17.75" (45.1 cm)
Weight with foam 45 lbs. (20.41 kg)	Weight without foam 31.5 lbs. (14.29 kg)	Buoyancy Max. 530.89 lbs. (240.81 kg)
Range Temperature -20 / 140° F (-29 / 60° C)	No. of Wheels 2	Retractable Handle YES

iM3075 Pelican Storm Transport Case Certificates

• MIL-STD-810F • FED-STD-101C • ATA 300

iM3075 Pelican Storm Transport Case Accessories

Cat. #	Description
iM-LIDSTAY	Lid Stay
iM-VALVE-M-B	Manual Purge Valve
iM3075-DIV	Padded Dividers
iM3075-FOAM	Replacement Foam
iM30XX-BEZEL	Base Bezel Kit
iM30XX-BEZEL-LID	Lid Bezel Kit
iM30XX-UTILIT YORG	Utility Organizer